

ALL PURPOSE ADHESIVE CO.

ENCapSeal™ Warranty

All Purpose Adhesive Company (APAC) warrants to the original owner of the installation that ENCapSeal™ will reduce a floor's moisture emissions from a high of eight pounds per 24 hour per 1000 square feet to as low as three pounds as measured per the anhydrous calcium chloride test ASTM 1869-98. Moisture emissions testing must be done prior to the installation of ENCapSeal™ with results less than eight pounds. ENCapSeal™ can also be used and is warranted for application over hard, well-bonded adhesive residue, including "cutback" residue. ENCapSeal™ will bond and encapsulate existing adhesive residue to form a protective barrier against migration. Apply ENCapSeal and allow to dry for 48 hours prior to the application of any patching compounds. If an installational failure (loss of adhesion) occurs as the direct result of the product supplied by APAC, All Purpose Adhesive Company will pay to replace the flooring in problem areas and will pay for reasonable labor as determined by our company. ENCapSeal™ is warranted for five-years. Warranty period is extended to seven-years when these premium APAC adhesives are used: A-2001, A-2000, A-440, A-440SF, U-984, A-757, A-671, A-610, A-564, A-539, A-530, A-510, VG-551 and EZ-471.

This warranty applies to installations made after June 1, 2003 for floor covering sold as regulars or first quality. The use of seconds, damaged goods, or trial runs will void this warranty. Copies of purchase invoices for floor covering indicating date purchased, purchase price, name and style of materials, and factory lot numbers should be retained by purchaser for future reference and warranty claim verification.

Provisions:

1. Substrate to be prepared following industry standards and adhesive manufacturer's floor preparation procedures and recommended guidelines.
2. Directions on our label and individual product specification sheets must be strictly followed.
3. Installations shall be performed in a professional manner by qualified installation technicians.
4. Claims should be submitted to the adhesive distributor in written form, giving the date of the installation, location and size of installation with names and phone numbers of all parties relevant to the claim.
5. Warranty registration must be completed and returned to All Purpose Adhesive Co. within 15 days from installation.

Exclusion: This warranty does not cover bond failure caused by abnormal use, nor bond failure caused by cleaning chemicals, or cleaning practices not approved by the floor covering and adhesive manufacturer. This warranty does not cover bond failure directly attributable to manufacturing defects in the floor covering. We exclude incidental or consequential damages under this warranty. Some states do not allow these exclusions; therefore, the above limitations may not apply. To qualify for the warranty, the batch numbers of the product in question must be supplied to All Purpose Adhesive Company. APAC reserves the right to inspect any installation by an APAC representative or an authorized inspector as determined by our company.

* Residue: defined as residual staining that is left after all adhesive has been scraped away down to the concrete surface.



revised 02-15-05

All Purpose Adhesive Company • 2424 Lakeland Road • Dalton, GA 30721 • 800-747-APAC • fax: 706-277-4157
www.apacadhesives.com • apac@apacadhesives.com

APAC's WARRANTED BONDING SYSTEM

APAC'S Extended Warranty for 7-Years with ENCapSeal™

Use the following APAC Premium Professional Grade Adhesives with ENCapSeal™.

For Carpet Bonds:

- ENCapSeal™
- EZ-471, 440, 440SF, 2000 or 2001
- EZ-771 or 613 Seam Sealer

For Carpet Module Bonds:

- ENCapSeal™
- 610 Pressure Sensitive Adhesive or
EZ-671 Spray Grade Pressure Sensitive Adhesive

For Vinyl (Felt-Back) Bonds:

- ENCapSeal™
- VG-551 Adhesive

For VCT Bonds:

- ENCapSeal™
- 539 ECOlogical Premium Clear Thin Spread or
530 Premium Clear Thin Spread Adhesive

For Traditional Wood Bonds:

- ENCapSeal™
- 757 Engineered Wood Flooring Adhesive

For Ultimate Wood Bonds:

- ENCapSeal™
- U-984 Universal Urethane Wood Adhesive

For Ceramic Tile Bonds:

- ENCapSeal™
- CerimaGrip 460

For Luxury Vinyl and Vinyl Plank Bonds:

- ENCapSeal™
- 564 Universal Resilient Floor Adhesive